

FIXED TWIST-LOCK DIMMING RECEPTACLE

JL-240SXB



PRODUCT SUMMARY

All the JL-240SXB photocontrol receptacle was designed for the lanterns those intended to have an ANSI C136.10 receptacle to fit a twist-lock photocontrol. This product conforms newly published ANSI C136.41 to allow a LED lamp multi-controlled through the receptacle.

This series offers 2 gold-plated low voltage pads on the top surface to fit photocontrol has ANSI C136.41 conforming spring contacts, and offers 2 wiring leads at rear side for signal connection. Especially, this product does not occupy any space inside the lantern for those cases less internal space available.

FEATURES

- Glass-Fiber strongen PBT
- Gilded Pads made from phophor bronze Nickel plated and gilded over 0.7um
- Gold plating per ASTM B 522
- Silicone gasket applied to flange
- Shorter body design for slim fixtures

SPECIFICATIONS

Model No.	JL-240SXB
Applicable Volt Range	0~480VAC
Rated Frequency	50/60Hz
Load Rating	15A
Signal Control	0-30 VDC, 250 mA Max
Lead	16AWG,14AWG 6" min
Ambient Temperature	-40°C ~ +70°C
Related Humidity	96%
Outdoor Wiring Cable	●
Certifications	<div>CB CE UK CA</div>