

FLAGSHIP SLIM DIMMING RECEPTACLE

JL-260D



PRODUCT SUMMARY

This JL-260D series photocontrol receptacle is designed for the lanterns those intended to have an ANSI C136.10 receptacle to fit a twist-lock photocontrol. it conforms newly published ANSI C136.41 to allow a LED lamp multi-controlled through the receptacle.

It offers 2 or 4 gold-plated low voltage pads on the top surface to fit photocontrol has ANSI C136.41 conforming spring contacts, and offers 2 or 4 wiring leads at rear side for signal connection. Especially, it is featured with waterproof self-rotation and 360° limited, while a super compressed height size is offered.

D1 type is an integral structure, with external thread installation.Type D2 is a split structure for internal thread installation.

FEATURES

- Body made from polycarbonate
- Contacts made from phosphor bronze
- Gold pad made from Nickel plated phosphor bronze with gold plating per ASTM B 522
- High light North pointer

SPECIFICATIONS

Model No.	JL-260D
Applicable Volt Range	0~480VAC
Rated Frequency	50/60Hz
Load Rating	15A
Signal Control	0-30 VDC, 250 mA Max
Lead	16AWG/14AWG 6" min
Ambient Temperature	-40°C ~ +70°C
Related Humidity	96%
Certifications	ANSI C136.41-2013   CB  