

SWIVELED WIRE-IN ELECTRONIC PHOTOCONTROL

JL-404C



PRODUCT SUMMARY

The Photocontrol JL-404C is applicable to control the street lighting, passage lighting and doorway lighting automatically in accordance with the ambient lighting level. This product is designed with electronic circuits. Its quicker response with time delay of 3-10 seconds offers easy-to-test feature. Especially, model JL-404C provides a wide voltage range for customer applications under almost power supplies. Further, a preset 3-10 seconds time-delay might avoid mis-operation due to spotlight or lightning during the night time This product has been listed by UL LLC and is comply with the Standard for Non-industrial Photoelectric Switches for Lighting Control UL773A.

FEATURES

- 3~10s Time-delay preventing redundant turning-off caused by headlights or lightning
- Swivel Incorporated

SPECIFICATIONS

Model No.	JL-404C
Rated Voltage	120~277VAC
Available Voltage Range	105~305VAC
Rated Frequency	50/60Hz
Rated Loading	500W Tungsten, 850VA Ballast 5A e-Ballast
Power Consumption	1.8W@120VAC
Operate Levels	10~20Lx Turn-On / 30~80Lx Turn-Off
Ambient Temperature	-40°C ~ +70°C
Related Humidity	96%
Leads	AWG #18,105°C 4" min
Wire Color Coding	US
Failure Mode	Fail-Off
Certifications	  