

## MINIATURE IMPROVED ELECTRONIC DIRECT WIRE-IN PHOTOCONTROL JL-412C(R)



JL-412C



JL-412CR



### PRODUCT SUMMARY

The photocontrol JL-412C(R) is applicable to control the passage lighting and doorway lighting automatically in accordance with the ambient lighting level.

This product is designed with electronic circuits. Its quicker response with time delay of 3-10 seconds offers easy-to-test feature, while a miniature profile supports most smaller fixtures. Further, a preset 3-10 seconds time-delay might avoid redundancy operation due to spotlight or lightning during the night time

This product has been listed by UL LLC and is comply with the Standard for Non-industrial Photoelectric Switches for Lighting Control UL773A.

Its R version provides a separated sensor assembly.

### FEATURES

- UL773A direct wire-in
- 120~277V Multi-Volts
- IR-Filtered Phototransistor Sensor
- IP65 protection
- Miniature size

### SPECIFICATIONS

Model No.	JL-412C	JL-412CR
Rated Voltage	120~277VAC	
Available Voltage Range	105~305VAC	
Rated Frequency	50/60Hz	
Rated Loading	1.2A Tungsten / Ballast	1A e-Ballast
Power Consumption	1W Max.	
On-off Levels	10~30Lx Turn-On / 30~80Lx Turn-Off	
Ambient Temperature	-40°C ~ +70°C	
Related Humidity	96%	
Leads Length	AWG #18,AWM1430	
Wire Color Coding	US	
Certifications	  	