

ZHAGA BOOK-18 RECEPTACLE (700+RETAINER PLATE AND WASHER)

JL-700-K4/K5



JL-700-K4



JL-700-K5





PRODUCT SUMMARY

JI-700-K4/K5 locking socket meets the requirements of Zhaga Book-18 standard interface (Z-LEX-R, Z-LEX-C) and has passed relevant certification, which is convenient for the development and installation of road lighting, regional lighting or commercial and residential lighting, such as street lights, industrial and mining lights, corridor lights, wall lights, etc.

FEATURES

- Standardized interface defined in Zhaga Book–18
- Compact size allowing greater flexibility in luminaire design
- Advanced sealing to achieve IP66 with no mounting screws
- Scalable solution allows use of Ø40mm photocell and Ø80mm LEX-M in a central management system with the same connection interface
- Flexible mounting position, upwards, downwards and sideways facing
- Integrated single gasket that seals to both luminaire and module that minimizes assembling time

Specifications

Model No.	JL-700-K4/K5
Rated Voltage	24VDC
Rated current of interface	1.5A MAX
Ambient Temperature	−40°C ~ +70 °C
Related Humidity	96%
*Wires	AWM 1015,18/20/22 AWG,105°C AWM 1007,18/20/22 AWG,80°C
IP	IP66
Certifications	ZZhaga CB CE UK C

^{*}Conductor specification: # 20 conductor has UL certification